

4-Port Un-Managed POE Switch (ALPHA-POE-4F)



Key Feature of Switch:

4*10/100Mbps PoE ports, 2*10/100Mbps uplink port;
Support IEEE802.3af/at;
Support restrains network storm, VLAN function;
Max Transmission distance up to 250m with PoE Power;
Built-in power supply;
Maximum power of single PoE port: 30W;
Maximum PoE power: 75W;
Adopts store-and-forward architecture;
Fanless, natural cooling, small, compact, and quiet design
Suitable for desktop or wall;
Support lightning protection 6000V;

Technical Specification:

MODEL	ALPHA-POE-4A
Power Adapter Voltage	AC 110V-240V
Consumption	78W(52V 1.5A)
PoE Ethernet Port	1-4 port:10/100Mbps
Ethernet Port	Uplink port:10/100Mbps
Transmission Distance	100Mbps:0-100m / 10Mbps:0-250m / Uplink Port:0-100m
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u, IEEE802.3x, IEEE802.3ab
Switching Capacity	1.2Gbps
Packet Buffer Memory	1Mbits
Throughput	0.9Mbps
MAC Table	1K
Packet Forwarding rate	10Mbps:14880pps/port, 100Mbps:1488000pps/port
PoE Standard	IEEE802.3af/at
PoE Power Supply	1/2 +, 3/6 -, 8 core power supply
PoE Power	af=15.4w, at=30w for each port



ALPHA MAX TECHNOLOGIES PVT. LTD.

CIN No: U72900HR2021PTC095606; GSTIN: 07AAVCA3385L1ZY

Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
LED Indicator	LINK/ACT 100Mbps: PoE Status Indicator, Power Indicator, Extender
Environment Specification	Operating Temperature-0 C~55 C, Operating Humidity -20-95%, Storage Temperature: -20 C~70 C
Dimension(L*W*H)	202mm*140mm*45mm,
Color & Weight	Black 0.95Kg