

Datasheet of OPSC-H

Pictures

- ◆Support Gen11th Intel® Core™ I3/ i5/ i7 CPU
- ◆DP interface: DP1.4 supports 8K output
- ◆Type-C interface: support video transmission+USB3.0 transmission
- ◆Support HDMI+DP+JAE 80PIN All channels 4K60hz or above output
- ◆Support dual channel SO-DIMM DDR4 memory and M.2 SSD storage
- ◆Support JAE 80 PIN standard connection interface
- ◆Support TPM2.0



Specifications

General	CPU	Intel® Gen11th, Core™ i5 /i7 CPU 4 Core 8 Thread, 8 MB Intel® Smart Cache Power Consumption 28~35W, Main Frequency 3.1~4.4 GHz	
	Chipset	Integrated in CPU	
	Graphic	Intel® Iris® Xe Graphics	
	Memory	2 x SO-DIMM DDR4 2666 MT/s, Max 128GB	
	Storage	1 x M.2 2280 PCIE Slot, for NVME / SATA 1 x SATA Slot, for HDD/SSD	
	Display Output	1 x HDMI 2.0: 4K/60Hz; 1 x DP 1.4: 8K/60Hz	
	Ethernet	LAN	1 x 10/100/1000Mbps
WIFI		1 x M.2 2230 Slot, Support WiFi 2.4G & 5G , WIFI6 for Option	
Audio		HD Audio Support	
I/O Port	Interface	3 x USB 2.0, 3 x USB3.0, 1 x Type-C (USB 3.0 Video Out), 1 x HDMI, 1 x DP 1 x Line-out, 1 x Mic in, 1 x Gigabit Lan, 1 x Power On/Off.	
Power	Power supply	19V/4.7A	
Dimension	Size (mm)	OPSC: 195 x 180 x 30mm	UnitBox: 282*257*79MM
	Weight (kg)	N.W.≈1.2 Kg	G.W.≈1.4 Kg
Temperature/ humidity	Working temperature	0°C~ 45°C	
	Storage temperature	-40°C~ 80°C	
	Working humidity	10% - 95% @40°C, Non-condensing	
OS	Support	Windows 10/11 & Linux	

Note:
Product specifications are for reference only and subject to change without prior notice

